

TECHNICAL DATASHEET

TERMINAL BLOCK TYPE HKT 11/5

WISKA Hoppmann GmbH
Kisdorfer Weg 28
24568 Kaltenkirchen
Germany



Product designation:	Terminal Block
Type of terminal:	5-pole screw terminal
WISKA type:	HKT 11/5
Nominal cross-section:	4 mm ²
Rated insulation voltage:	450 V
Rated current:	32 A
Ambient temperature:	-30°C +85°C
Screw torque:	0,5 Nm
Test standard:	DIN EN 60998-1 (EN 60998-1 / IEC 60998-1) DIN EN 60998-2-1 (EN 60998-2-1 / IEC 60998-2-1)

Number of conductors per terminal point / pole

Cross-section [mm ²]:	1,5			2,5			4		
	s	r	f	s	r	f	s	r	f
Conductor type ^{A)} :									
Minimal	1	1	1	1	1	1	1	1	1
Maximum	5	4	4	4	3	3	2	2	2

^{A)} s = solid, r = rigid, f = flexible (with wire-end ferrules)

WISKA part No.:	50108887
Spare part No.:	22001132
Material: Terminal base:	Copper-zinc alloy (brass), uncoated
Terminal housing:	Polyamide with GWIT = 850°C
Screws:	Steel, zinc-plated
Terminal holder:	Polyamide with GWIT = 850°C
Supplier: 201626	Terminal: 112-02082000 Terminal holder: 112-02130000
Suitable for:	COMBI 108, COMBI 206, COMBI 304, COMBI 308, COMBI 407

